

# Pneumatic Breakers



## 4-Bolt High Performance Models

| MODEL   | Standard hex chuck size (in) | Retainer type | Air inlet (in) | Length (in) | Weight (lb) | Part no.     |
|---|------------------------------|---------------|----------------|-------------|-------------|--------------|
| <b>CP 0112—30-pound class—air consumption at 90 psi: 45 cfm</b> |                              |               |                |             |             |              |
| CP 0112   | 7/8 x 3 1/4                  | Latch         | 3/4 NPT        | 20          | 30          | 8900 0030 26 |
| CP 0112 EX  | 7/8 x 3 1/4                  | Latch         | 3/4 NPT        | 20          | 30          | 8900 0030 27 |
| CP 0112   | 1 x 4 1/4                    | Latch         | 3/4 NPT        | 20          | 30          | 8900 0030 23 |
| CP 0112 EX  | 1 x 4 1/4                    | Latch         | 3/4 NPT        | 30 3/8      | 33          | 8900 0030 24 |
| CP 0112 S   | 1 x 4 1/4                    | Kick Latch    | 3/4 NPT        | 20          | 31          | 8900 0030 25 |

|   |           |       |         |        |    |              |
|---|-----------|-------|---------|--------|----|--------------|
| <b>CP 1210—35-pound class—air consumption at 90 psi: 48 cfm</b> |           |       |         |        |    |              |
| CP 1210   | 1 x 4 1/4 | Latch | 3/4 NPT | 21 1/8 | 44 | 8900 0030 01 |
| CP 1210S  | 1 x 4 1/4 | Latch | 3/4 NPT | 21 1/8 | 45 | 8900 0030 03 |
| CP 1210S  | 1 1/4 x 6 | Latch | 3/4 NPT | 23     | 46 | 8900 0030 09 |
| CP 1210S  | 1 1/8 x 6 | Latch | 3/4 NPT | 23     | 46 | 8900 0030 07 |
| CP 1210 SVR   | 1 x 4 1/4 | Latch | 3/4 NPT | 23 1/2 | 51 | 8900 0030 05 |
| CP 1210 SVR   | 1 1/8 x 6 | Latch | 3/4 NPT | 25 1/2 | 55 | 8900 0030 08 |
| CP 1210 SVR   | 1 1/4 x 6 | Latch | 3/4 NPT | 25 1/2 | 55 | 8900 0030 10 |

|   |           |       |         |    |    |              |
|---|-----------|-------|---------|----|----|--------------|
| <b>CP 1260—60-pound class—air consumption at 90 psi: 63 cfm</b> |           |       |         |    |    |              |
| CP 1260   | 1 1/8 x 6 | Latch | 3/4 NPT | 27 | 64 | 8900 0030 29 |
| CP 1260 S   | 1 1/8 x 6 | Latch | 3/4 NPT | 27 | 65 | 8900 0030 31 |
| CP 1260 SVR   | 1 1/8 x 6 | Latch | 3/4 NPT | 29 | 75 | 8900 0030 33 |
| CP 1260   | 1 1/4 x 6 | Latch | 3/4 NPT | 27 | 64 | 8900 0030 28 |
| CP 1260 S   | 1 1/4 x 6 | Latch | 3/4 NPT | 27 | 65 | 8900 0030 30 |
| CP 1260 SVR   | 1 1/4 x 6 | Latch | 3/4 NPT | 29 | 75 | 8900 0030 32 |

|   |           |       |         |    |    |              |
|---|-----------|-------|---------|----|----|--------------|
| <b>CP 1290—90-pound class—air consumption at 90 psi: 81 cfm</b> |           |       |         |    |    |              |
| CP 1290   | 1 1/8 x 6 | Latch | 3/4 NPT | 29 | 82 | 8900 0030 38 |
| CP 1290 S   | 1 1/8 x 6 | Latch | 3/4 NPT | 29 | 83 | 8900 0030 40 |
| CP 1290 SVR   | 1 1/8 x 6 | Latch | 3/4 NPT | 31 | 96 | 8900 0030 42 |
| CP 1290   | 1 1/4 x 6 | Latch | 3/4 NPT | 29 | 82 | 8900 0030 37 |
| CP 1290 S   | 1 1/4 x 6 | Latch | 3/4 NPT | 29 | 83 | 8900 0030 39 |
| CP 1290 SVR   | 1 1/4 x 6 | Latch | 3/4 NPT | 31 | 96 | 8900 0030 41 |

EX = Extended handle for trench work; S = Silenced models; SVR = Silenced & Vibration Reduced models  
Spike Drivers also available, CP 1260 S SPDR 8900 0030 34, CP 1269 S SPDR 8900 0030 43  
Note: CP 1230 / CP 1240 replaced by CP 1260 / CP 1290

CP four-bolt breakers require minimal servicing to maintain peak operating efficiency over extended periods of rugged use.

Durable polyurethane front-head springs, side bolts and anvil minimize repairs.

CP breakers can be ordered with mufflers, or mufflers can be purchased separately.

**Retrofit dust suppression spray kits**  
see page 21



Standard model  
CP 0112



Standard model  
CP 1210, 1260 and 1290



CP1210S

### CP 0112 and CP 1210

The CP 0112 (30-pound class) and CP 1210 (35-pound class) demolition tools are lightweight yet rugged. They're designed for light to medium construction and plant maintenance work such as demolition of floors, pavement, bridge maintenance, asphalt, frozen ground and masonry walls. They're very popular for bridge deck jobs. CP 0112 EX has an extended handle for trench work.

- Alloy steel forgings provide excellent durability
- Four-bolt backhead design withstands rugged use
- CP 0112 is equipped with an integral oiler that provides continuous lubrication
- Heavy-duty front headsprings on CP 1210 reduce reaction back to operator
- CP 1210S is equipped with a silencer to reduce sound level
- Vibration reduced handle (SVR) is available on the CP 1210 SVR

### CP 1260 and CP 1290

The CP 1260 (60-pound class) and CP 1290 (90-pound class) demolition tools are engineered to deliver the power and durability necessary for a variety of construction and plant maintenance applications such as breaking heavy and reinforced concrete, frozen ground, asphalt, boulders and pavement.

- Alloy steel forgings provide excellent durability
- Four-bolt backhead design withstands rugged use
- Integral oiler provides continuous lubrication
- Durable polyurethane front headsprings reduce reaction back to operator
- Reversible piston reduces maintenance cost
- Air inlet swivel for easy maneuverability
- CP 1260 S and CP 1290 S are equipped with silencers
- Vibration reduced handle (SVR) available on the CP 1260 SVR and CP 1290 SVR



Breakers can be ordered with mufflers or mufflers can be purchased separately. Refer to page 5 for part numbers.



Vibration reduced models (VRS) are also silenced.  
1210 SVR  
1260 SVR  
1290 SVR