

Hydraulic Power Packs

Why tow a large compressor to the site if you don't need to? The CP hydraulic power pack couldn't be more convenient. For site-to-site transportation, two people can lift it into a truck. On-site, the CP power pack can easily be wheeled around by one person.

CP hydraulic power packs are available in gasoline, diesel or electrically driven versions, and provide portable power for a long list of applications in the 5-10 gpm/2000-2500 psi range.

HOW ARE THEY TO OPERATE?

Couldn't be simpler. The thermostatically controlled oil cooler gives fast warm-up and helps prevent the hydraulic oil from overheating. Correct working temperature is achieved within minutes – even during the winter. The variable flow on/off valve allows for simple tool changes and slow start up. A gauge shows when it's time to change the filter.

WHAT ABOUT FUEL CONSUMPTION?

Many of the power packs are equipped with Power On Demand. This system automatically idles the engine when the tool is not being used and speeds it up when the tool is activated. It saves fuel and keeps noise to a minimum.



MODEL		PAC P9	PAC P13	PAC P18	PAC P18 Twin
Engine		9 HP, Honda gasoline	13 HP, Honda gasoline	18 HP, B&S Vanguard gasoline	18 HP, B&S Vanguard gasoline
Weight (incl oil)	lb	160	192	243	270
Dimensions (LxWxH)	in	23.0x20.7x26.8	27.7x23.6x29.3	28.3x27.6x29.3	28.3x27.6x29.3
Oil flow	gpm	5	5-8	5-10	2 x 5 or 1 x 10
Maximum pressure	psi	2200	2200	2200	2200
Fuel capacity	US gal	1.5	1.8	1.9	1.9
HTMA Type		I	I / II	I / II	I / II
Hose included		No	No	No	No
Power on Demand (POD)		Yes	Yes	No	No
Oil control: engine oil		Yes	Yes	No	No
Electric start		No	No	Yes	Yes
Part number ¹⁾		1807 0080 26	1807 0110 25	1807 0160 34	1807 0160 27